

## Aerial Lift Safety Training Glendale

Aerial Lift Safety Training Glendale - There are around 26 to 30 construction fatalities in North America attributed to the utilization of aerial lifts. Nearly all of the individuals killed are craftsmen like for instance laborers, painters, electrical workers, carpenters or ironworkers. Most fatalities are caused by tip-overs, electrocutions and falls. The greatest hazard is from boom-supported lifts, such as bucket trucks and cherry pickers. Nearly all fatalities are related to this particular kind of lift, with the rest involving scissor lifts. Other dangers include being thrown out of a bucket, being struck by falling things, and being caught between the lift bucket or guardrail and a thing, like for instance a steel beam or joist.

In order to operate an aerial lift safely, carry out a check on the following items prior to making use of the device: operating and emergency controls, safety devices (e.g., guardrails and outriggers), personal fall protection gear, and tires and wheels. Inspect for possible leaks in the air, hydraulic fluid and fuel-system. Inspect the device for loose or missing parts.

The areas that worker will utilize the aerial device should be checked thoroughly for potential hazards, such as holes, bumps, debris and drop-offs. Overhead powerlines have to be monitored and avoided. It is suggested that aerial lift devices be used on stable, level surfaces. Don't work on steep slopes that exceed slope limits that the manufacturer specified. Even on a level slope, outriggers, brakes and wheel chocks should be set.

Employers are needed to provide aerial lift operators and maintenance mechanics with the right instruction manuals. Operators and mechanics need to be trained by a certified person experienced with the relevant aerial lift model.

### Aerial Lift Safety Tips:

- o Close lift platform chains or doors prior to operating.
- o Climbing on and leaning over guardrails is prohibited. Stand on the platform or floor of the bucket.
- o Use the provided manufacturer's load-capacity restrictions.
- o When working near traffic, utilize proper work-zone warnings, like for example cones and signs.

Electrocutions are preventable if safety procedures are followed. Stay well away from power lines - at least 10 feet. Trained electrical workers must de-energize and/or insulate power lines. Workers must utilize personal protective equipment and tools, like insulated bucket. Nonetheless, a bucket which is insulated does not protect from electrocution if, for instance, the person working touches a different wire providing a path to the ground.

Falls are avoidable if the individual working remains secure in guardrails or within the bucket by making use of a full-body harness or a positioning device. If there is an anchorage inside the bucket, a positioning belt along with a short lanyard is acceptable.

Tip-overs are preventable by following the manufacturer's directions. Unless the manufacturer specifies otherwise, never drive whilst the lift platform is elevated. Follow the device's vertical and horizontal reach restrictions, and never go beyond the load-capacity which is specified.